




Elbows 90°, Long Radius
Rohrbogen
nach ASME / ANSI B 16.9



Nominal Size Abmessung	Outside Diameter Außendurchmesser	Identification Kennzeichnung	Wall Thickness Wanddicke	Radius	Length Höhe	Kilos/Piece kg/Stück
	mm		mm			
	<i>D</i>		<i>S</i>			
				<i>A</i>	<i>K</i>	
1/2"	21,3	STD	2,77	38	48	0,08
		XS	3,73			0,10
		SCH 160	4,78			0,12
3/4"	26,7	STD	2,87	38	51	0,08
		XS	3,91			0,10
		SCH 160	5,56			0,14
1"	33,4	STD	3,38	38	56	0,15
		XS	4,55			0,20
		SCH 160	6,35			0,26
		XXS	9,09			0,38
1 1/4"	42,2	STD	3,56	48	70	0,26
		XS	4,85			0,34
		SCH 160	6,35			0,38
		XXS	9,7			0,58
1 1/2"	48,3	STD	3,68	57	83	0,38
		XS	5,08			0,48
		SCH 160	7,14			0,64
		XXS	10,16			0,90
2"	60,3	STD	3,91	76	106	0,68
		XS	5,54			0,91
		SCH 160	8,74			1,32
		XXS	11,07			1,68
2 1/2"	73,0	STD	5,16	95	132	1,33
		XS	7,01			1,73
		SCH 160	9,52			2,35
		XXS	14,02			3,06
3"	88,9	STD	5,49	114	159	2,08
		XS	7,62			2,78
		SCH 160	11,13			3,75
		XXS	15,24			5,18
4"	114,3	STD	6,02	152	210	3,95
		XS	8,56			5,40
		SCH 120	11,13			6,80
		SCH 160	13,59			9,00
		XXS	17,12			10,30



Elbows 90°, Long Radius
Rohrbogen
 nach ASME / ANSI B 16.9

Nominal Size Abmessung	Outside Diameter Außendurchmesser	Identification Kennzeichnung	Wall Thickness Wanddicke	Radius	Length Höhe	Kilos/Piece kg/Stück
	mm		mm			
	<i>D</i>		<i>S</i>			
5"	141,3	STD	6,55	190	262	6,67
		XS	9,52			9,34
		SCH 120	12,7			12,00
		SCH 160	15,88			14,70
		XXS	19,05			17,20
6"	168,3	STD	7,11	229	313	10,40
		XS	10,97			15,50
		SCH 120	14,27			19,50
		SCH 160	18,26			26,00
		XXS	21,95			29,90
8"	219,1	SCH 20	6,35	305	414	16,20
		STD	8,18			20,90
		SCH 60	10,31			26,30
		XS	12,7			31,30
		SCH 100	15,09			38,20
		SCH 120	18,26			45,40
		XXS	22,22			54,40
SCH 160	23,01	55,90				
10"	273,0	SCH 20	6,35	381	518	25,30
		STD	9,27			37,00
		XS	12,7			49,40
		SCH 80	15,09			61,30
		SCH 100	18,26			68,60
		SCH 120	21,44			83,50
		XXS	25,4			92,80
		SCH 160	28,58			103,00
12"	323,9	SCH 20	6,35	457	619	35,90
		STD	9,53			54,00
		SCH 40	10,31			58,15
		XS	12,7			71,20
		SCH 60	14,27			82,26
		SCH 80	17,48			94,70
		SCH 100	21,44			115,00
		XXS	25,4			134,00
SCH 160	33,32	181,00				
14"	355,6	STD	9,52	457	619	69,90
		SCH 40	11,13			83,06
		XS	12,7			91,60
		SCH 80	19,05			132,00
		SCH 100	23,83			171,23
		SCH 120	27,79			188,00
		SCH 160	35,71			247,70



Elbows 90°, Long Radius
Rohrbogen
nach ASME / ANSI B 16.9

Nominal Size Abmessung	Outside Diameter Außendurchmesser	Identification Kennzeichnung	Wall Thickness Wanddicke	Radius	Length Höhe	Kilos/Piece kg/Stück
	mm		mm			
	<i>D</i>		<i>S</i>			
16"	406,4	STD	9,52	610	813	91,20
		XS	12,7			120,00
		SCH 60	16,66			153,00
		SCH 80	21,44			195,00
		SCH 100	26,19			235,00
		SCH 120	30,96			274,00
		SCH 140	36,53			334,80
18"	457,2	STD	9,52	686	914	116,00
		XS	12,7			153,00
		SCH 40	14,27			176,21
		SCH 60	19,05			232,70
		SCH 80	23,83			273,00
		SCH 100	29,36			350,64
		SCH 120	34,93			382,50
20"	508,0	STD	9,52	762	1016	144,00
		XS	12,7			190,00
		SCH 60	20,62			311,02
		SCH 80	26,19			372,00
22"	558,8	STD	9,52	838	1118	174,60
		XS	12,7			230,40
		SCH 100	34,92			623,00
24"	609,6	STD	9,52	914	1219	208,00
		XS	12,7			275,00
		SCH 30	14,27			298,00
		SCH 60	24,61			451,00
		SCH 80	30,96			510,00