




Elbows 90°, Short Radius
Rohrbogen
 nach ASME / ANSI B 16.9



Nominal Size Abmessung	Outside Diameter Außendurchmesser	Identification Kennzeichnung	Wall Thickness Wanddicke	Radius A	Length Höhe K	Kilos/Piece kg/Stück
	mm		mm			
	D		S			
1"	33,4	STD	3,38	25	41	0,15
		XS	4,55			0,20
		SCH 160	6,35			0,26
1 1/4"	42,2	STD	3,56	32	52	0,26
		XS	4,85			0,34
		SCH 160	6,35			0,38
1 1/2"	48,3	STD	3,68	38	62	0,38
		XS	5,08			0,48
		SCH 160	7,14			0,64
2"	60,3	STD	3,91	51	81	0,68
		XS	5,54			0,91
		SCH 160	8,74			0,32
2 1/2"	73	STD	5,16	64	100	1,33
		XS	7,01			1,73
		SCH 160	11,13			3,75
3"	88,9	STD	5,49	76	121	2,08
		XS	7,62			2,78
		SCH 160	11,13			3,75
4"	114,3	STD	6,02	102	159	3,95
		XS	8,56			5,40
		SCH 160	13,59			5,62
5"	141,3	STD	6,55	127	197	6,67
		XS	9,52			9,34
		SCH 160	13,59			15,50
6"	168,3	STD	7,11	152	237	10,40
		XS	10,97			15,50
		SCH 160	18,26			24,20
8"	219,1	STD	8,18	203	313	20,90
		XS	12,7			31,30
		SCH 160	23,01			55,90
10"	273,0	STD	9,27	254	391	37,00
		XS	12,7			49,00
		SCH 160	23,01			54,00
12"	323,9	STD	9,53	305	467	54,00
		XS	12,7			71,20
		SCH 160	23,01			69,90
14"	355,6	STD	9,52	356	533	69,90
		SCH 40	11,13			83,06
		XS	12,7			91,60
16"	406,4	STD	9,52	610	813	91,20
		XS	12,7			120,00
		SCH 160	23,01			116,00
18"	457,2	STD	9,52	457	686	116,00
		XS	12,7			153,00
		SCH 40	14,27			176,21
20"	508,0	STD	9,52	508	762	144,00
		XS	12,7			190,00
		SCH 160	23,01			208,00
24"	609,6	STD	9,52	610	914	208,00
		XS	12,7			275,00
		SCH 160	23,01			275,00